

Fig.A.6.1.9 Transmitter Spurious Emission - Conducted (802.11g, Ch6, Center Frequency)




Fig.A.6.1.10 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 30 MHz-26 GHz)

GHz)




Fig.A.6.1.11 Transmitter Spurious Emission - Conducted (802.11g, Ch11, Center Frequency)




Fig.A.6.1.12 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 30 MHz-26 GHz)




Fig.A.6.1.13 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Fig.A.6.1.14 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-26 GHz)




Fig.A.6.1.15 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Fig.A.6.1.16 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.17 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.18 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-26 GHz)




Fig.A.6.1.19 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Fig.A.6.1.20 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-26 GHz)




Fig.A.6.1.21 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Fig.A.6.1.22 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.23 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)




Fig.A.6.1.24 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-26 GHz)

SISO ANT1:




Fig.A.6.1.25 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Fig.A.6.1.26 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-26 GHz)




Fig.A.6.1.27 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Fig.A.6.1.28 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.29 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.30 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-26 GHz)




Fig.A.6.1.31 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Fig.A.6.1.32 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-26 GHz)




Fig.A.6.1.33 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Fig.A.6.1.34 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.35 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)




Fig.A.6.1.36 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-26 GHz)

MIMO ANT0:




Fig.A.6.1.37 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Fig.A.6.1.38 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-26 GHz)




Fig.A.6.1.39 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Fig.A.6.1.40 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.41 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.42 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-26 GHz)




Fig.A.6.1.43 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Fig.A.6.1.44 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-26 GHz)




Fig.A.6.1.45 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Fig.A.6.1.46 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.47 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)




Fig.A.6.1.48 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-26 GHz)

MIMO ANT1:




Fig.A.6.1.49 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Fig.A.6.1.50 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-26 GHz)




Fig.A.6.1.51 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Fig.A.6.1.52 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.53 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.54 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-26 GHz)




Fig.A.6.1.55 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)




Fig.A.6.1.56 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-26 GHz)




Fig.A.6.1.57 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)




Fig.A.6.1.58 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-26 GHz)




Fig.A.6.1.59 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)




Fig.A.6.1.60 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-26 GHz)

.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.



Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as

appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360° . For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

Final radiated emissions measurements

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} + Cable Loss + Antenna Factor

Where:

P_{Mea} field strength recorded from the instrument

EUT ID:02a

Measurement Results:

Conclusion: Pass

802.11b

Average

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17972.500	45.02	-25.50	46.70	23.82	54.00	8.98	H
9808.000	42.66	-33.50	38.00	38.16	54.00	11.34	H
14382.500	39.48	-28.40	42.30	25.58	54.00	14.52	H
12979.000	35.36	-30.50	39.20	26.66	54.00	18.64	H
7477.500	31.75	-34.50	36.80	29.45	54.00	22.25	H
2389.600	42.02	-20.00	28.10	34.02	54.00	11.98	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.500	45.80	-25.50	46.70	24.60	54.00	8.20	H
9808.000	42.72	-33.50	38.00	38.22	54.00	11.28	H
14362.500	39.51	-28.40	42.30	25.61	54.00	14.49	V
12746.500	35.62	-30.50	39.10	27.02	54.00	18.38	V
7574.000	32.08	-35.00	36.90	30.28	54.00	21.92	V
4431.000	29.67	-37.60	32.40	34.87	54.00	24.33	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17990.500	45.03	-25.50	46.70	23.83	54.00	8.97	H
9808.000	41.48	-33.50	38.00	36.98	54.00	12.52	V
14375.000	39.78	-28.40	42.30	25.88	54.00	14.22	H
12964.500	35.48	-30.50	39.20	26.78	54.00	18.52	H
7986.500	31.51	-34.80	37.10	29.21	54.00	22.49	H
2487.900	42.12	-20.00	28.30	33.82	54.00	11.88	V

802.11g

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.000	45.17	-25.50	46.70	23.97	54.00	8.83	H
9808.000	42.60	-33.50	38.00	38.10	54.00	11.40	H
14402.000	40.09	-28.60	42.50	26.19	54.00	13.91	H
12954.500	35.55	-30.50	39.20	26.85	54.00	18.45	H
7513.000	31.52	-34.50	36.80	29.22	54.00	22.48	H
2390.000	43.75	-20.00	28.10	35.75	54.00	10.25	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17994.000	45.11	-25.50	46.70	23.91	54.00	8.89	V
9808.000	42.99	-33.50	38.00	38.49	54.00	11.01	H
14385.000	39.68	-28.40	42.30	25.78	54.00	14.32	V
12949.000	35.66	-30.50	39.20	26.96	54.00	18.34	V
7973.000	31.84	-34.80	37.10	29.54	54.00	22.16	V
4961.000	27.60	-37.10	33.30	31.40	54.00	26.40	H

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17998.000	45.13	-25.50	46.70	23.93	54.00	8.87	H
9808.000	42.80	-33.50	38.00	38.30	54.00	11.20	H
14373.000	39.84	-28.40	42.30	25.94	54.00	14.16	V
12952.500	35.74	-30.50	39.20	27.04	54.00	18.26	V
7576.500	32.02	-35.00	36.90	30.22	54.00	21.98	V
2485.000	43.08	-20.00	28.30	34.78	54.00	10.92	V

802.11n-HT20

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.500	45.10	-25.50	46.70	23.90	54.00	8.90	H
9808.000	43.10	-33.50	38.00	38.60	54.00	10.90	H
14396.000	39.77	-28.60	42.50	25.87	54.00	14.23	H
12664.500	35.67	-30.50	39.10	27.07	54.00	18.33	H
7914.000	31.57	-34.90	37.10	29.37	54.00	22.43	H
2390.000	42.74	-20.00	28.10	34.74	54.00	11.26	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.500	45.31	-25.50	46.70	24.11	54.00	8.69	V
9808.000	42.89	-33.50	38.00	38.39	54.00	11.11	H
14506.000	39.91	-28.60	42.50	26.01	54.00	14.09	H
12964.000	35.56	-30.50	39.20	26.86	54.00	18.44	V
7547.000	32.52	-35.00	36.90	30.72	54.00	21.48	V
4397.500	29.77	-37.90	32.40	35.27	54.00	24.23	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17989.000	45.31	-25.50	46.70	24.11	54.00	8.69	H
9808.000	43.11	-33.50	38.00	38.61	54.00	10.89	H
14400.000	40.09	-28.60	42.50	26.19	54.00	13.91	H
12962.500	35.61	-30.50	39.20	26.91	54.00	18.39	H
7987.000	31.75	-34.80	37.10	29.45	54.00	22.25	H
2485.000	42.52	-20.00	28.30	34.22	54.00	11.48	V

802.11n-HT40

Ch3

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17998.500	45.69	-25.50	46.70	24.49	54.00	8.31	V
9808.000	43.20	-33.50	38.00	38.70	54.00	10.80	H
14373.500	39.84	-28.40	42.30	25.94	54.00	14.16	V
12988.500	35.56	-30.50	39.20	26.86	54.00	18.44	H
7550.000	32.23	-35.00	36.90	30.43	54.00	21.77	V
2389.200	45.02	-20.00	28.10	37.02	54.00	8.98	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17997.000	45.31	-25.50	46.70	24.11	54.00	8.69	H
9808.000	42.96	-33.50	38.00	38.46	54.00	11.04	H
14367.500	39.75	-28.40	42.30	25.85	54.00	14.25	H
12899.000	35.53	-30.70	39.10	27.03	54.00	18.47	H
7519.500	31.74	-34.50	36.80	29.44	54.00	22.26	H
3228.500	28.01	-38.50	30.40	36.11	54.00	25.99	V

Ch9

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17994.000	45.00	-25.50	46.70	23.80	54.00	9.00	H
9808.000	42.83	-33.50	38.00	38.33	54.00	11.17	H
14381.500	39.70	-28.40	42.30	25.80	54.00	14.30	H
12647.500	35.45	-30.50	39.10	26.85	54.00	18.55	H
7592.000	31.66	-35.00	36.90	29.86	54.00	22.34	H
2485.500	43.06	-20.00	28.30	34.76	54.00	10.94	V

Peak

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17819.500	55.70	-25.50	46.70	34.50	74.00	18.30	H
14525.500	50.86	-28.60	42.50	36.96	74.00	23.14	H
9808.500	46.82	-33.50	38.00	42.32	74.00	27.18	H
12178.000	46.59	-31.40	39.00	38.99	74.00	27.41	H
7577.500	43.13	-35.00	36.90	41.33	74.00	30.87	H
2369.400	55.28	-20.10	28.00	47.28	74.00	18.72	H

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17975.500	56.25	-25.50	46.70	35.05	74.00	17.75	H
14415.000	51.26	-28.60	42.50	37.36	74.00	22.74	H
9808.000	47.21	-33.50	38.00	42.71	74.00	26.79	H
12262.500	46.62	-31.40	39.00	39.02	74.00	27.38	V
5971.500	44.85	-36.10	34.40	46.55	74.00	29.15	V
4423.000	40.47	-37.60	32.40	45.67	74.00	33.53	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17971.500	56.34	-25.50	46.70	35.14	74.00	17.66	V
14775.000	50.90	-28.30	41.30	37.90	74.00	23.10	H
12506.500	46.98	-31.20	38.90	39.28	74.00	27.02	H
9808.000	46.67	-33.50	38.00	42.17	74.00	27.33	V
7968.000	42.19	-34.80	37.10	39.89	74.00	31.81	V
2494.000	54.61	-20.00	28.30	46.31	74.00	19.39	V

802.11g

Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17949.000	55.44	-25.50	46.70	34.24	74.00	18.56	H
14421.000	51.35	-28.60	42.50	37.45	74.00	22.65	H
9808.500	47.26	-33.50	38.00	42.76	74.00	26.74	H
12672.500	46.82	-30.50	39.10	38.22	74.00	27.18	H
7995.000	43.18	-34.80	37.10	40.88	74.00	30.82	H
2389.900	58.24	-20.00	28.10	50.24	74.00	15.76	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17952.000	56.18	-25.50	46.70	34.98	74.00	17.82	H
14114.500	50.96	-29.00	42.00	37.96	74.00	23.04	V
9808.000	47.12	-33.50	38.00	42.62	74.00	26.88	H
12706.500	47.05	-30.50	39.10	38.45	74.00	26.95	H
7963.500	43.19	-34.80	37.10	40.89	74.00	30.81	V
3994.500	40.71	-38.20	32.50	46.41	74.00	33.29	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17942.500	56.54	-25.50	46.70	35.34	74.00	17.46	H
14389.500	50.74	-28.40	42.30	36.84	74.00	23.26	V
12940.500	47.63	-30.50	39.20	38.93	74.00	26.37	V
9808.500	47.10	-33.50	38.00	42.60	74.00	26.90	H
5996.500	45.89	-36.00	34.50	47.39	74.00	28.11	V
2485.800	55.63	-20.00	28.30	47.33	74.00	18.37	V

802.11n-HT20
Ch1

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17992.500	55.42	-25.50	46.70	34.22	74.00	18.58	H
14669.500	50.53	-27.30	41.90	35.93	74.00	23.47	H
9808.000	47.32	-33.50	38.00	42.82	74.00	26.68	H
12734.500	47.27	-30.50	39.10	38.67	74.00	26.73	H
7260.000	43.09	-35.00	36.50	41.49	74.00	30.91	H
2389.700	55.07	-20.00	28.10	47.07	74.00	18.93	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17976.000	56.18	-25.50	46.70	34.98	74.00	17.82	H
14500.500	51.13	-28.60	42.50	37.23	74.00	22.87	V
9808.000	47.59	-33.50	38.00	43.09	74.00	26.41	H
12341.500	47.42	-31.10	38.90	39.62	74.00	26.58	H
5990.000	45.49	-36.10	34.40	47.19	74.00	28.51	V
4011.500	40.92	-38.20	32.50	46.62	74.00	33.08	V

Ch11

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17890.500	56.07	-25.50	46.70	34.87	74.00	17.93	H
14320.500	51.20	-28.40	42.30	37.30	74.00	22.80	H
12969.500	47.63	-30.50	39.20	38.93	74.00	26.37	H
9808.500	46.92	-33.50	38.00	42.42	74.00	27.08	H
7551.000	42.75	-35.00	36.90	40.95	74.00	31.25	H
2485.400	54.99	-20.00	28.30	46.69	74.00	19.01	V

802.11n-HT40

Ch3

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17995.000	56.62	-25.50	46.70	35.42	74.00	17.38	V
14492.000	51.25	-28.60	42.50	37.35	74.00	22.75	H
9808.500	47.34	-33.50	38.00	42.84	74.00	26.66	H
12846.000	47.25	-30.70	39.10	38.75	74.00	26.75	V
5983.500	46.47	-36.10	34.40	48.17	74.00	27.53	V
2388.900	58.02	-20.00	28.10	50.02	74.00	15.98	V

Ch6

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17977.500	56.46	-25.50	46.70	35.26	74.00	17.54	V
14671.000	51.63	-27.30	41.90	37.03	74.00	22.37	H
9808.000	47.97	-33.50	38.00	43.47	74.00	26.03	H
12224.000	46.90	-31.40	39.00	39.30	74.00	27.10	V
6648.500	43.24	-35.60	35.40	43.44	74.00	30.76	V
3996.000	41.54	-38.20	32.50	47.24	74.00	32.46	V

Ch9

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17921.500	55.69	-25.50	46.70	34.49	74.00	18.31	H
14471.000	51.14	-28.60	42.50	37.24	74.00	22.86	H
9808.500	47.36	-33.50	38.00	42.86	74.00	26.64	H
12969.000	46.56	-30.50	39.20	37.86	74.00	27.44	H
7584.000	43.03	-35.00	36.90	41.23	74.00	30.97	H
2485.000	55.53	-20.00	28.30	47.23	74.00	18.47	V

Sample calculation: 802.11n 40MHz CH9–Peak, 17921.500 MHz

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(34.49 \text{ dBuV/m}) + \text{Cable Loss}(-25.50) + \text{Antenna Factor}(46.70) = 55.69 \text{ dBuV/m}$$


A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

Setup:

A stand-alone EUT shall be placed in the center along the back edge of the tabletop. For multiunit tabletop systems, the EUT shall be centered laterally (left to right facing the tabletop) on the tabletop and its rear shall be flush with the rear of the table.

Accessories that are part of an EUT system tested on a tabletop shall be placed in a test arrangement on one or both sides of the host with a 10 cm separation between the nearest points of the cabinets. The rear of the host and accessories shall be flush with the back of the supporting tabletop unless that would not be typical of normal use. If more than two accessories are present, then an equipment test arrangement shall be chosen that maintains 10 cm spacing between cabinets unless the equipment is normally located closer together.



Exploratory ac power-line conducted emission measurements

Exploratory measurements shall be used to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement. For each mode of operation and for each ac power current-carrying conductor, cable manipulation shall be performed within the range of likely configurations. For this measurement or series of measurements, the frequency spectrum of interest shall be monitored looking for the emission that has the highest amplitude relative to the limit. Once that emission is found for each

current-carrying conductor of each power cord associated with the EUT (but not the cords associated with non-EUT equipment in the overall system), the one configuration and arrangement and mode of operation that produces the emission closest to the limit over all of the measured conductors shall be recorded.

Final ac power-line conducted emission measurements

Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation. If the EUT is composed of equipment units that have their own separate ac power connections (e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network), then each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be measured separately. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:
WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.420000	41.6	L1	19.9	15.8	57.4
0.537000	45.1	L1	19.9	10.9	56.0
1.068000	36.3	L1	19.6	19.7	56.0
1.680000	40.6	L1	19.5	15.4	56.0
2.481000	39.5	L1	19.5	16.5	56.0
3.660000	39.1	L1	19.5	16.9	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.411000	38.1	L1	19.9	9.5	47.6
0.541500	42.6	L1	19.9	3.4	46.0
0.951000	33.4	L1	19.6	12.6	46.0
2.049000	31.7	L1	19.5	14.3	46.0
2.139000	30.3	L1	19.5	15.7	46.0
3.687000	30.7	L1	19.5	15.3	46.0




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.388500	45.9	L1	19.9	12.2	58.1
0.532500	46.8	L1	19.9	9.2	56.0
1.063500	38.2	L1	19.6	17.8	56.0
2.575500	43.9	L1	19.5	12.1	56.0
4.888500	35.7	L1	19.6	20.3	56.0
6.859500	28.1	L1	19.5	31.9	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.388500	37.6	L1	19.9	10.5	48.1
0.541500	42.7	L1	19.9	3.3	46.0
1.122000	33.2	L1	19.5	12.8	46.0
2.094000	31.8	L1	19.5	14.2	46.0
2.575500	34.9	L1	19.5	11.1	46.0
3.642000	29.2	L1	19.5	16.8	46.0

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p> <p>NVLAP® </p> <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2017</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <table><tr><td><p>2020-09-29 through 2021-09-30 Effective Dates</p></td><td></td><td><p> For the National Voluntary Laboratory Accreditation Program</p></td></tr></table>		<p>2020-09-29 through 2021-09-30 Effective Dates</p>		<p> For the National Voluntary Laboratory Accreditation Program</p>
<p>2020-09-29 through 2021-09-30 Effective Dates</p>		<p> For the National Voluntary Laboratory Accreditation Program</p>		

END OF REPORT