

TEST REPORT

FCC MPE Test for IL7SF
Certification

APPLICANT
LG Electronics Inc.

REPORT NO.
HCT-RF-2101-FC121-R1

DATE OF ISSUE
February 5, 2021

Tested by
Jin Gwan Lee



Technical Manager
Jong Seok Lee



HCT CO., LTD.

Soo Chan Lee
SooChan Lee / CEO

HCT CO., LTD.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC MPE Test for
IL7SF

REPORT NO.

HCT-RF-2101-FC121-R1

DATE OF ISSUE

February 05, 2021

Additional Model

-

Applicant**LG Electronics Inc.**

222, LG-ro, Jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, 451-713, Korea

**Eut Type
Model Name**

Silverbox RADIO ASM-RECEIVER
IL7SF

FCC ID

BEJIL7SF2

Frequency range

2 402 MHz ~ 2 480 MHz (Bluetooth)
2 412 MHz ~ 2 462 MHz (WLAN)
5 180 MHz ~ 5 825 MHz (UNII)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue | Description |
|--------------|-------------------|-----------------------------------|
| 0 | January 28, 2021 | Initial Release |
| 1 | February 05, 2021 | Revised the Worst case on page 11 |

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID : BEJIL7SB2 report.

RF Exposure Statement

1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

| Frequency range (MHz) | Electric field Strength (V/m) | Magnetic field Strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--------------------------|----------------------------------|----------------------------------|--|-----------------------------|
| 0.3 - 1.34..... | 614 | 1.63 | *(100) | 30 |
| 1.34 - 30..... | 824/f | 2.19/f | *(180/ f ²) | 30 |
| 30 - 300..... | 27.5 | 0.073 | 0.2 | 30 |
| 300 - 1500..... | | | f/1500 | 30 |
| 1500 - 100.000..... | | | 1.0 | 30 |

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. RESULTS

3-1. Bluetooth

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 6.500 | dBm |
| Average output Power at antenna input terminal | 4.467 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 2 402 ~ 2 480 | MHz |
| Antenna Gain(typical) | 5.400 | dBi |
| Antenna Gain(numeric) | 3.467 | - |
| Power density at prediction frequency(S) | 0.00308 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 11.900 | (dBm) |
| ERP | 9.75 | (dBm) |
| ERP | 0.009 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 25.02 | (dB) |

3-2. WLAN DTS Band (802.11b,g,n) SISO Internal Antenna

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 18.000 | dBm |
| Average output Power at antenna input terminal | 63.096 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 2 412 ~ 2 462 | MHz |
| Antenna Gain(typical) | 5.400 | dBi |
| Antenna Gain(numeric) | 3.467 | - |
| Power density at prediction frequency(S) | 0.04352 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 23.400 | (dBm) |
| ERP | 21.25 | (dBm) |
| ERP | 0.133 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 13.52 | (dB) |

3-3. WLAN DTS Band (802.11b,g,n) SISO External Antenna

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 18.000 | dBm |
| Average output Power at antenna input terminal | 63.096 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 2 412 ~ 2 462 | MHz |
| Antenna Gain(typical) | 1.200 | dBi |
| Antenna Gain(numeric) | 1.318 | - |
| Power density at prediction frequency(S) | 0.01655 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 19.200 | (dBm) |
| ERP | 17.05 | (dBm) |
| ERP | 0.051 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 17.72 | (dB) |

3-4. WLAN DTS Band (802.11b,g,n) MIMO

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 21.000 | dBm |
| Average output Power at antenna input terminal | 125.893 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 2 412 ~ 2 462 | MHz |
| Antenna Gain(typical) | 5.400 | dBi |
| Antenna Gain(numeric) | 3.467 | - |
| Power density at prediction frequency(S) | 0.08684 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 26.400 | (dBm) |
| ERP | 24.25 | (dBm) |
| ERP | 0.266 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 10.52 | (dB) |

3-5. UNII Band 3(802.11a,n,ac) SISO Internal Antenna

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 21.500 | dBm |
| Average output Power at antenna input terminal | 141.254 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 5 745 ~ 5 825 | MHz |
| Antenna Gain(typical) | 5.400 | dBi |
| Antenna Gain(numeric) | 3.467 | - |
| Power density at prediction frequency(S) | 0.09744 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 26.900 | (dBm) |
| ERP | 24.75 | (dBm) |
| ERP | 0.299 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 10.02 | (dB) |

3-6. UNII Band 2C (802.11a,n,ac) SISO External Antenna

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 20.500 | dBm |
| Average output Power at antenna input terminal | 112.202 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 5 500 ~ 5 720 | MHz |
| Antenna Gain(typical) | 1.400 | dBi |
| Antenna Gain(numeric) | 1.380 | - |
| Power density at prediction frequency(S) | 0.03081 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 21.900 | (dBm) |
| ERP | 19.75 | (dBm) |
| ERP | 0.094 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 15.02 | (dB) |

3-7. UNII Band 3 (802.11a,n,ac) MIMO

| | | |
|---|---------------|--------------------|
| Average output Power at antenna input terminal | 23.000 | dBm |
| Average output Power at antenna input terminal | 199.526 | mW |
| Prediction distance | 20.000 | cm |
| Prediction frequency | 5 745 ~ 5 825 | MHz |
| Antenna Gain(typical) | 5.400 | dBi |
| Antenna Gain(numeric) | 3.467 | - |
| Power density at prediction frequency(S) | 0.13764 | mW/cm ² |
| MPE limit for uncontrolled exposure at prediction frequency | 1.000 | mW/cm ² |

2.1091

| | | |
|-----------|--------|-------|
| EIRP | 28.400 | (dBm) |
| ERP | 26.25 | (dBm) |
| ERP | 0.422 | (W) |
| ERP Limit | 3.00 | (W) |
| MARGIN | 8.52 | (dB) |

Worst Case: Simultaneous MPE 20cm is

BT (0.00308 mW/cm²) + 5G WLAN (0.13764 mW/cm²)= 0.14072 < 1