




RADIO EXPOSURE TEST REPORT

FCC ID : MSQ-RTBE7900
Equipment : BE3600 Dual Band WiFi 7 Router
Brand Name : ASUS
Model Name : RT-BE58U, TUF-BE3600, RT-BE3600
Applicant : ASUSTeK COMPUTER INC.
1F., No. 15, Lide Rd., Beitou, Taipei City 112, Taiwan
Standard : 47 CFR Part 2.1091

The product was received on Apr. 12, 2024, and testing was started from Apr. 23, 2024 and completed on Jun. 21, 2024. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Antenna Information	5
1.3 Table for Multiple Listing	7
1.4 Table for EUT Supports Function.....	7
1.5 Accessories	8
1.6 Applicable Standards	8
1.7 Testing Location	8
2 Maximum Permissible Exposure	9
2.1 Limit of Maximum Permissible Exposure	9
2.2 MPE Calculation Method.....	9
2.3 MPE Exemption.....	10
2.4 Calculated Result and Limit.....	11

Photographs of EUT v01



History of this test report

TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A1_1 Ver1.1

Page Number : 3 of 11
Issued Date : Jul. 02, 2024
Report Version : 01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Muse Chan



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5250 5250-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)

1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	XINSHENG	SSR-2402018	Dipole Antenna	I-PEX	Note 1
2	XINSHENG	SSR-2402020	Dipole Antenna	I-PEX	
3	XINSHENG	SSR-2402019	Dipole Antenna	I-PEX	
4	XINSHENG	SSR-2402021	Dipole Antenna	I-PEX	

Note 1:

Ant.	Port		Gain (dBi)				
	2.4GHz	5GHz	2.4GHz	5GHz UNII 1	5GHz UNII 2A	5GHz UNII 2C	5GHz UNII 3
1	1	-	3.37	-	-	-	-
2	-	1	-	2.91	3.37	2.99	3.08
3	2	-	3.46	-	-	-	-
4	-	2	-	3.11	3.20	3.09	3.10

Note 2: The above information was declared by manufacturer.

Note 3: Directional gain information

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ant}} \left\{ \sum_{k=1}^{N_{ant}} g_{j,k} \right\}^2}{N_{ANT}} \right]$
BF	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ant}} \left\{ \sum_{k=1}^{N_{ant}} g_{j,k} \right\}^2}{N_{ANT}} \right]$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ant}} \left\{ \sum_{k=1}^{N_{ant}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

Ex.

Directional Gain (NSS1) formula :

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ant}} \left\{ \sum_{k=1}^{N_{ant}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

$$NSS1(g1,1) = 10^{G1/20} ; NSS1(g1,2) = 10^{G2/20} ; NSS1(g1,2) = 10^{G3/20} ; NSS1(g1,2) = 10^{G4/20}$$

$$g_{j,k} = (NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2$$

$$DG = 10 \log[(NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2 / N_{ANT}] \Rightarrow 10$$

$$\log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / N_{ANT}]$$

Where ;

$$2.4G \ G1 = 3.37 \text{ dBi} ; G2 = 3.46 \text{ dBi} ;$$

$$5G \text{ UNII-1} \ G1 = 2.91 \text{ dBi} ; G2 = 3.11 \text{ dBi} ;$$

$$5G \text{ UNII-2A} \ G1 = 3.37 \text{ dBi} ; G2 = 3.20 \text{ dBi} ;$$

$$5G \text{ UNII-2C} \ G1 = 2.99 \text{ dBi} ; G2 = 3.09 \text{ dBi} ;$$

$$5G \text{ UNII-3} \ G1 = 3.08 \text{ dBi} ; G2 = 3.10 \text{ dBi} ;$$

$$2.4G \ DG = 6.43 \text{ dBi}$$

$$5G \text{ UNII-1} \ DG = 6.02 \text{ dBi}$$

$$5G \text{ UNII-2A} \ DG = 6.30 \text{ dBi}$$

$$5G \text{ UNII-2C} \ DG = 6.05 \text{ dB}$$

$$5G \text{ UNII-3} \ DG = 6.10 \text{ dBi}$$

Note 4: For 2.4GHz function:

For IEEE 802.11 b/g/n/VHT/ax/be (2TX/2RX):

Port 1~2 can be used as transmitting/receiving antenna.

Port 1~2 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax/be (2TX/2RX):

Port 1~2 can be used as transmitting/receiving antenna.

Port 1~2 could transmit/receive simultaneously.



1.3 Table for Multiple Listing

The model names in the following table are identical to each other in all aspects except for the following table:

EUT	Model Name	Housing design	Way to fix Antenna cable to port	LED spacer thickness	Power button size
1	RT-BE58U	Housing design 1	Note 4	Thick	Small
-	RT-BE3600				
2	TUF-BE3600	Housing design 2		Thin	Big

Note 1: The different model names (RT-BE58U and RT-BE3600) served as strategy for marketing.

Note 2: From the above models, model: RT-BE58U (EUT 1) was selected as representative model for the test and its data was recorded in this report.

Note 3: The above information was declared by manufacturer.

Note 4:

EUT	Model Name	Way to fix Antenna cable to port
1	RT-BE58U	Ant.1: Fix the antenna cable on the holder in RC1 Ant.2: Fix the antenna cable on the holder in RC5
-	RT-BE3600	Ant.3: Fix the antenna cable on the holder in RC6 Ant.4: Fix the antenna cable on the holder in RC4
2	TUF-BE3600	Ant.1: Fix the antenna cable on the holder of the heatsink Ant.2: Fix the antenna cable on the holder of the heatsink Ant.3: Fix the antenna cable on the holder in RC6 and on the holder of the heatsink Ant.4: Fix the antenna cable on the holder in RC4 and on the holder of the heatsink

1.4 Table for EUT Supports Function

Function	Support Type
AP Router	Master
Bridge	Slave without radar detection
Repeater	Master
Mesh	Master

Note 1: The USB port on this device supports both storage and WWAN functionality.

Note 2: The above information was declared by manufacturer.



1.5 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
Adapter 1	Frecom	F24L6-120200SPAU	Input: 100-240V, 50/60Hz, 0.6A Output: 12.0V, 2.0A, 24.0W
Adapter 2	KEYU	KA2401A-1202000US	Input: 100-240V, 50/60Hz, 0.65A Max Output: 12V, 2000mA
Other			
RJ-45 cable*1: Non-Shielded, 1.5m			

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.7 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) TEL: 886-3-656-9065 FAX: 886-3-656-9085 Test site Designation No. TW3787 with FCC. Conformity Assessment Body Identifier (CABID) TW3787 with ISCED.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 51 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For Mode 1: WLAN 2.4GHz + WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	6.43	28.36	32.64	0.50	2060.630	51	C	4994.0	0.4128
5.2G;D1D	6.02	28.89	32.76	0.50	2118.361	51	C	4994.0	0.4243
5.3G;D1D	6.30	23.62	27.77	0.07	608.135	51	C	4994.0	0.1218
5.6G;D1D	6.05	23.91	27.81	0.03	608.135	51	C	4994.0	0.1218
5.8G;D1D	6.10	29.87	33.82	0.02	2421.029	51	C	4994.0	0.4850

Simultaneous Transmission Analysis Mode:

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	6.43	28.36	32.64	0.50	2060.630	51	C	4994.0	0.4128
5.8G;D1D	6.10	29.87	33.82	0.02	2421.029	51	C	4994.0	0.4850
Sum TL Ratio_C	0.8978								
Ratio Limit	1								

For Mode 2: WLAN 2.4GHz + WLAN 5GHz + WWAN

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	6.43	28.36	32.64	0.50	2060.630	51	C	4994.0	0.4128
5.2G;D1D	6.02	28.89	32.76	0.50	2118.361	51	C	4994.0	0.4243
5.3G;D1D	6.30	23.62	27.77	0.07	608.135	51	C	4994.0	0.1218
5.6G;D1D	6.05	23.91	27.81	0.03	608.135	51	C	4994.0	0.1218
5.8G;D1D	6.10	29.87	33.82	0.02	2421.029	51	C	4994.0	0.4850
Band12;G7D	0.00	24.00	21.85	0.50	171.791	51	C	2327.2	0.0738

Simultaneous Transmission Analysis Mode:

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	6.43	28.36	32.64	0.50	2060.630	51	C	4994.0	0.4128
5.8G;D1D	6.10	29.87	33.82	0.02	2421.029	51	C	4994.0	0.4850
Band12;G7D	0.00	24.00	21.85	0.50	171.791	51	C	2327.2	0.0738
Sum TL Ratio_C	0.9716								
Ratio Limit	1								

Note: The above antenna gain was declared by manufacturer.

————THE END————