



FCC PART 15C TEST REPORT

BLUETOOTH LOW ENERGY (BLE) PART

No. 25T04Z100217-038

for

TCL Communication Ltd.

GSM/UMTS/LTE mobile phone

Model Name: T517F

FCC ID: 2ACCJB237

with

Hardware Version: 05

Software Version: 3A4G

Issued Date: 2025-3-27

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email:ctl_terminals@caict.ac.cn, website: www.chinattl.com

REPORT HISTORY

| Report Number | Revision | Description | Issue Date |
|----------------------|-----------------|--------------------------------------|-------------------|
| 25T04Z100217-038 | Rev.0 | 1st edition | 2025-3-24 |
| 25T04Z100217-038 | Rev.1 | Add test plot for duty cycle in B.10 | 2025-3-27 |

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

| | |
|---|-----------|
| 1. TEST LABORATORY | 5 |
| 1.1. INTRODUCTION & ACCREDITATION | 5 |
| 1.2. TESTING LOCATION | 5 |
| 1.3. TESTING ENVIRONMENT | 6 |
| 1.4. PROJECT DATA | 6 |
| 1.5. SIGNATURE | 6 |
| 2. CLIENT INFORMATION | 7 |
| 2.1. APPLICANT INFORMATION | 7 |
| 2.2. MANUFACTURER INFORMATION | 7 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 8 |
| 3.1. ABOUT EUT | 8 |
| 3.2. INTERNAL IDENTIFICATION OF EUT | 8 |
| 3.3. INTERNAL IDENTIFICATION OF AE | 8 |
| 3.4. NORMAL ACCESSORY SETTING | 8 |
| 3.5. GENERAL DESCRIPTION | 8 |
| 4. REFERENCE DOCUMENTS | 9 |
| 4.1. DOCUMENTS SUPPLIED BY APPLICANT | 9 |
| 4.2. REFERENCE DOCUMENTS FOR TESTING | 9 |
| 5. TEST RESULTS | 10 |
| 5.1. SUMMARY OF EUT MODE | 10 |
| 5.2. SUMMARY OF TEST RESULTS | 10 |
| 5.3. STATEMENTS | 10 |
| 6. TEST FACILITIES UTILIZED | 11 |
| 7. MEASUREMENT UNCERTAINTY | 12 |
| 7.1. PEAK OUTPUT POWER - CONDUCTED | 12 |
| 7.2. FREQUENCY BAND EDGES - CONDUCTED | 12 |
| 7.3. TRANSMITTER SPURIOUS EMISSION - CONDUCTED | 12 |
| 7.4. RADIATED UNWANTED EMISSION | 12 |
| 7.5. 6dB BANDWIDTH | 12 |
| 7.6. MAXIMUM POWER SPECTRAL DENSITY LEVEL | 12 |
| 7.7. AC POWERLINE CONDUCTED EMISSION | 13 |
| ANNEX A: EUT PARAMETERS | 14 |
| ANNEX B: DETAILED TEST RESULTS | 15 |
| B.1. MEASUREMENT METHOD | 15 |
| B.2. PEAK OUTPUT POWER | 16 |
| B.3. FREQUENCY BAND EDGES - CONDUCTED | 17 |



No. 25T04Z100217-038

| | |
|--|-----------|
| B.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED | 19 |
| B.5. RADIATED UNWANTED EMISSION | 28 |
| B.6. 6dB BANDWIDTH..... | 33 |
| B.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL | 36 |
| B.8. AC POWERLINE CONDUCTED EMISSION | 39 |
| B.9. ANTENNA REQUIREMENT | 43 |
| B.10. DUTY CYCLE | 44 |
| ANNEX C: ACCREDITATION CERTIFICATE | 45 |



No. 25T04Z100217-038

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

1.3. Testing Environment

Normal Temperature: 20-27℃
Relative Humidity: 20-50%

1.4. Project data

Testing Start Date: 2025-2-10
Testing End Date: 2025-3-24

1.5. Signature



Wu Le
(Prepared this test report)



Sun Zhenyu
(Reviewed this test report)



Hu Xiaoyu
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
Contact: Ting Wang
Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: +86 755 36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address /Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
Contact: Ting Wang
Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: +86 755 36612000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|-----------------------------|-----------------------------|
| Description | GSM/UMTS/LTE mobile phone |
| Model Name | T517F |
| FCC ID | 2ACCJB237 |
| Frequency Band | ISM 2400MHz~2483.5MHz |
| Type of Modulation(LE mode) | GFSK (Bluetooth Low Energy) |
| Number of Channels(LE mode) | 40 |
| Power Supply | 3.91V DC by Battery |
| Antenna gain | -0.3dBi |

3.2. Internal Identification of EUT

| EUT ID* | SN or IMEI | HW Version | SW Version | Date of receipt |
|---------|-------------------------------------|------------|------------|-----------------|
| UT17a | 356956250000570/ 356956250000588 | 05 | 3A4G | 2025-3-10 |
| UT06a | 356956250000039/ 356956250000125 | 05 | 3A4G | 2025-2-10 |

EUT2*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

| AE ID* | Description | Model | Manufacturer |
|--------|-------------|---------------|---|
| AE1 | Battery1 | TLp050C7 | Dongguan Veken Battery Co., Ltd. |
| AE2 | Battery2 | TLp050CB | Shenzhen Aerospace Electronic Co., Ltd. |
| AE3 | Charger1 | QC13US-N | ShenZhen BajunDa Electronics Co.,Ltd |
| AE4 | USB Cable1 | JWUB1686-M01R | Huizhou Juwei Electronics Co.,Ltd |
| AE5 | USB Cable2 | FKY-23-367 | Qiyang Fukangyuan Electronic Technology Co., Ltd. |

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery is used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of GSM/UMTS/LTE mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters, referring to Annex A for detailed information, is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

| Reference | Title | Version |
|-------------|--|-----------|
| FCC Part15 | FCC CFR 47, Part 15, Subpart C: | 2024 |
| | 15.205 Restricted bands of operation; | |
| | 15.209 Radiated emission limits, general requirements; | |
| | 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz. | |
| ANSI C63.10 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices | June,2013 |

5. Test Results

5.1. Summary of EUT Mode

Two modes are provided:

| Mode | Conditions |
|--------|------------|
| Mode A | 1Mbps |
| Mode B | 2Mbps |

*For the test results, the EUT had been tested all conditions. But only the worst case (Mode A) was shown in test report except the "Peak Output Power" test was shown all conditions.

5.2. Summary of Test Results

Abbreviations used in this clause:

P Pass, The EUT complies with the essential requirements in the standard.

F Fail, The EUT does not comply with the essential requirements in the standard

NA Not Applicable, The test was not applicable

NP Not Performed, The test was not performed by CTTL

| SUMMARY OF MEASUREMENT RESULTS | Sub-clause | Verdict |
|---|------------------------|----------|
| Peak Output Power | 15.247 (b)(1) | P |
| Frequency Band Edges- Conducted | 15.247 (d) | P |
| Transmitter Spurious Emission - Conducted | 15.247 (d) | P |
| Radiated Unwanted Emission | 15.247, 15.205, 15.209 | P |
| 6dB Bandwidth | 15.247 (a)(2) | P |
| Maximum Power Spectral Density Level | 15.247(e) | P |
| AC Powerline Conducted Emission | 15.107, 15.207 | P |
| Antenna Requirement | 15.203 | P |

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.3. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

6. Test Facilities Utilized

Conducted test system

| No. | Equipment | Model | Serial Number | Manufacturer | Calibration Period | Calibration Due date |
|-----|------------------------|--------|---------------|--------------|--------------------|----------------------|
| 1 | Vector Signal Analyzer | FSQ26 | 100024 | R&S | 1 year | 2026-03-09 |
| 2 | Test Receiver | ESCI | 100766 | R&S | 1 year | 2025-04-18 |
| 3 | LISN | ENV216 | 101459 | R&S | 1 year | 2025-05-16 |
| 4 | Shielding Room | S81 | / | ETS-Lindgren | / | / |

Radiated emission test system

| No. | Equipment | Model | Serial Number | Manufacturer | Calibration Period | Calibration Due date |
|-----|---------------|--------------------|----------------|--------------|--------------------|----------------------|
| 1 | Test Receiver | ESW44 | 103015 | R&S | 1 year | 2026-01-15 |
| 2 | EMI Antenna | VULB 9163 | 01176 | SCHWARZBECK | 1 year | 2025-04-07 |
| 3 | EMI Antenna | 3117 | 00058888 | ETS-Lindgren | 1 year | 2025-09-18 |
| 4 | EMI Antenna | LB-180400 -25-C-KF | 211008400 0006 | A-INFO | 1 year | 2025-05-22 |

7. Measurement Uncertainty

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

| | |
|-------------------------------|--------|
| Measurement Uncertainty (k=2) | 0.66dB |
|-------------------------------|--------|

7.2. Frequency Band Edges - Conducted

Measurement Uncertainty:

| | |
|-------------------------------|--------|
| Measurement Uncertainty (k=2) | 0.66dB |
|-------------------------------|--------|

7.3. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

| Frequency Range | Uncertainty (k=2) |
|-------------------|-------------------|
| 30 MHz ~ 8 GHz | 1.22dB |
| 8 GHz ~ 12.75 GHz | 1.51dB |
| 12.7GHz ~ 26 GHz | 1.51dB |

7.4. Radiated Unwanted Emission

Measurement Uncertainty:

| Frequency Range | Uncertainty(dBm) (k=2) |
|---|------------------------|
| 9kHz-30MHz | 3.96 |
| $30\text{MHz} \leq f \leq 1\text{GHz}$ | 5.29 |
| $1\text{GHz} \leq f \leq 18\text{GHz}$ | 5.62 |
| $18\text{GHz} \leq f \leq 40\text{GHz}$ | 3.52 |

7.5. 6dB Bandwidth

Measurement Uncertainty:

| | |
|-------------------------------|----------|
| Measurement Uncertainty (k=2) | 61.936Hz |
|-------------------------------|----------|

7.6. Maximum Power Spectral Density Level

Measurement Uncertainty:

| | |
|-------------------------------|--------|
| Measurement Uncertainty (k=2) | 0.66dB |
|-------------------------------|--------|

7.7. AC Powerline Conducted Emission

Measurement Uncertainty:

| | |
|-------------------------------|--------|
| Measurement Uncertainty (k=2) | 3.10dB |
|-------------------------------|--------|



No. 25T04Z100217-038

ANNEX A: EUT parameters

Disclaimer: The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.


ANNEX B: Detailed Test Results

B.1. Measurement Method

B.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



B.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The EUT was placed on a non-conductive table with 80cm above the ground plane for measurement below 1GHz and 1.5m above the ground plane for measurement above 1GHz. The measurement antenna was placed at a distance of 3 meters from the EUT. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated from 0° to 360° and the measurement antenna is moved from 1m to 4m to get the maximization result. The maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

B.2. Peak Output Power

B.2.1. Peak Output Power – Conducted

Method of Measurement: See ANSI C63.10-clause 11.9.1.1

- Set the RBW = 3 MHz.
- Set VBW = 10 MHz.
- Set span = 10 MHz.
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

Measurement Limit:

| Standard | Limit (dBm) |
|-----------------------|-------------|
| FCC Part 15.247(b)(3) | < 30 |

Measurement Results:

For GFSK

| Sample Rate | Channel No. | Frequency (MHz) | Peak Conducted Output Power (dBm) | Conclusion |
|-------------|-------------|-----------------|-----------------------------------|------------|
| 1Mbps | 0 | 2402 | -3.46 | P |
| | 19 | 2440 | -2.40 | P |
| | 39 | 2480 | -3.64 | P |
| 2Mbps | 1 | 2404 | -3.43 | P |
| | 19 | 2440 | -2.47 | P |
| | 38 | 2478 | -3.39 | P |

Conclusion: PASS

B.2.2. E.I.R.P.

The radiated E.I.R.P. is listed below:

Antenna gain = -0.3dBi

For GFSK

| Sample Rate | Channel No. | Frequency (MHz) | E.I.R.P. (dBm) | Conclusion |
|-------------|-------------|-----------------|----------------|------------|
| 1Mbps | 0 | 2402 | -3.76 | P |
| | 19 | 2440 | -2.70 | P |
| | 39 | 2480 | -3.94 | P |
| 2Mbps | 1 | 2404 | -3.73 | P |
| | 19 | 2440 | -2.77 | P |
| | 38 | 2478 | -3.69 | P |

Note: E.I.R.P. are calculated with the antenna gain.

Conclusion: PASS

B.3. Frequency Band Edges - Conducted

Method of Measurement: See ANSI C63.10-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 8MHz
- b) Sweep Time: Auto
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

| Standard | Limit (dBc) |
|----------------------------|-------------|
| FCC 47 CFR Part 15.247 (d) | < -20 |

Measurement Result:

For GFSK

| Channel No. | Frequency (MHz) | Hopping | Band Edge Power (dBc) | | Conclusion |
|-------------|-----------------|-------------|------------------------|--------|------------|
| 0 | 2402 | Hopping OFF | Fig.1 | -52.65 | P |
| 39 | 2480 | Hopping OFF | Fig.2 | -52.07 | P |

Conclusion: PASS

Test graphs as below




Fig.1. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off




Fig.2. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

B.4. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 11.11.2 and clause 11.11.3

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW = 300 kHz.
3. Set the span to ≥ 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum PSD level. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.
 2. Set VBW = 300 kHz.
 3. Set span to encompass the spectrum to be examined.
 4. Detector = peak.
 5. Trace Mode = max hold.
 6. Sweep = auto couple.
 7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

| Standard | Limit |
|----------------------------|---|
| FCC 47 CFR Part 15.247 (d) | 20dB below peak output power in 100 kHz bandwidth |

Measurement Results:

For GFSK

| Channel No. | Frequency (MHz) | Frequency Range | Test Results | Conclusion |
|-------------|-----------------|------------------|--------------|------------|
| 0 | 2402 | Center Frequency | Fig.3 | P |
| | | 30 MHz ~ 1 GHz | Fig.4 | P |
| | | 1 GHz ~ 3 GHz | Fig.5 | P |
| | | 3 GHz ~ 10 GHz | Fig.6 | P |
| | | 10GHz ~ 26 GHz | Fig.7 | P |
| 19 | 2440 | Center Frequency | Fig.8 | P |
| | | 30 MHz ~ 1 GHz | Fig.9 | P |
| | | 1 GHz ~ 3 GHz | Fig.10 | P |
| | | 3 GHz ~ 10 GHz | Fig.11 | P |
| | | 10GHz ~ 26 GHz | Fig.12 | P |
| 39 | 2480 | Center Frequency | Fig.13 | P |
| | | 30 MHz ~ 1 GHz | Fig.14 | P |
| | | 1 GHz ~ 3GHz | Fig.15 | P |
| | | 3 GHz ~ 10 GHz | Fig.16 | P |
| | | 10 GHz ~ 26 GHz | Fig.17 | P |

Conclusion: PASS

Test graphs as below




Fig.3. Transmitter Spurious Emission - Conducted: GFSK,2402MHz




Fig.4. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 30MHz - 1GHz




Fig.5. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 1GHz - 3GHz




Fig.6. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 3GHz - 10GHz




Fig.7. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 10GHz - 26GHz




Fig.8. Transmitter Spurious Emission - Conducted: GFSK, 2440MHz




Fig.9. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 30MHz - 1GHz




Fig.10. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 1GHz – 3GHz




Fig.11. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 3GHz – 10GHz




Fig.12. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 10GHz – 26GHz




Fig.13. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz




Fig.14. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 30MHz - 1GHz




Fig.15. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 1GHz - 3GHz




Fig.16. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 3GHz - 10GHz




Fig.17. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 10GHz - 26GHz

B.5. Radiated Unwanted Emission

Limits

Measurement Limit

| Standard | Limit |
|--|------------------------------|
| FCC 47 CFR Part 15.247, 15.205, 15.209 | 20dB below peak output power |

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band

| Frequency (MHz) | Field strength($\mu\text{V/m}$) | Measurement distance (m) |
|-----------------|-----------------------------------|--------------------------|
| 0.009 - 0.490 | $2400/F(\text{kHz})$ | 300 |
| 0.490 - 1.705 | $24000/F(\text{kHz})$ | 30 |
| 1.705 – 30.0 | 30 | 30 |

| Frequency of emission (MHz) | Field strength ($\mu\text{V/m}$) | Field strength (dB $\mu\text{V/m}$) | Measurement distance (m) |
|-----------------------------|------------------------------------|--------------------------------------|--------------------------|
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor.

Test setup




Figure B.5.1. Test Site Diagram (9kHz-30MHz)




Figure B.5.2. Test Site Diagram (30MHz-1GHz)




Figure B.5.3. Test Site Diagram (1GHz-40GHz)

Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10-2013 (ANSI C63.10-2020).

Test setting

| Frequency of emission (MHz) | RBW/VBW | Sweep Time(s) |
|-----------------------------|---------------|---------------|
| 30-1000 | 100kHz/300kHz | 5 |
| 1000-3000 | 1MHz/3MHz | 15 |
| 3000-18000 | 1MHz/3MHz | 40 |
| 18000-26500 | 1MHz/3MHz | 20 |

Sample Calculation

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea}+A_{Rpl}= P_{Mea}+Cable\ Loss+Antenna\ Factor$

Test note

1. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
2. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
3. Measurement frequencies were performed from 9 kHz to the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.

Test Result

EUT ID: UT17a

Average Measurement results

GFSK 2402MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2383.600 | 41.83 | -24.81 | 31.93 | 34.71 | 54.00 | 12.17 | V |
| 2389.600 | 42.33 | -24.76 | 31.96 | 35.14 | 54.00 | 11.67 | V |
| 4804.000 | 31.18 | -32.22 | 34.30 | 29.10 | 54.00 | 22.82 | V |
| 7206.000 | 32.70 | -29.88 | 35.60 | 26.98 | 54.00 | 21.30 | V |
| 9608.000 | 36.82 | -26.71 | 36.72 | 26.82 | 54.00 | 17.18 | V |
| 12010.000 | 35.91 | -27.34 | 38.62 | 24.63 | 54.00 | 18.09 | V |

GFSK 2440MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2435.200 | 42.53 | -25.20 | 32.14 | 35.59 | 54.00 | 11.47 | V |
| 2444.800 | 42.85 | -24.79 | 32.18 | 35.46 | 54.00 | 11.15 | V |
| 4882.000 | 30.78 | -32.18 | 34.24 | 28.73 | 54.00 | 23.22 | H |
| 7323.000 | 32.18 | -29.41 | 35.75 | 25.84 | 54.00 | 21.82 | H |
| 9764.000 | 34.78 | -28.13 | 37.07 | 25.84 | 54.00 | 19.22 | H |
| 12205.000 | 37.48 | -25.95 | 38.71 | 24.73 | 54.00 | 16.52 | V |

GFSK 2480MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2486.400 | 43.17 | -24.50 | 32.20 | 35.47 | 54.00 | 10.83 | V |
| 2488.000 | 43.20 | -24.47 | 32.20 | 35.47 | 54.00 | 10.80 | V |
| 4960.000 | 30.66 | -31.90 | 34.10 | 28.46 | 54.00 | 23.34 | V |

| | | | | | | | |
|-----------|-------|--------|-------|-------|-------|-------|---|
| 7440.000 | 32.75 | -28.77 | 35.68 | 25.85 | 54.00 | 21.25 | V |
| 9920.000 | 34.33 | -28.05 | 37.34 | 25.05 | 54.00 | 19.67 | V |
| 12400.000 | 36.04 | -27.32 | 38.70 | 24.67 | 54.00 | 17.96 | H |

Peak Measurement results

GFSK 2402MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2387.950 | 53.02 | -24.78 | 31.95 | 45.85 | 74.00 | 20.98 | H |
| 2389.800 | 52.85 | -24.76 | 31.96 | 45.65 | 74.00 | 21.15 | V |
| 4804.000 | 39.73 | -32.22 | 34.30 | 37.65 | 74.00 | 34.27 | V |
| 7206.000 | 41.73 | -29.88 | 35.60 | 36.01 | 74.00 | 32.27 | H |
| 9608.000 | 45.39 | -26.71 | 36.72 | 35.38 | 74.00 | 28.61 | V |
| 12010.000 | 44.86 | -27.34 | 38.62 | 33.58 | 74.00 | 29.14 | V |

GFSK 2440MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2434.400 | 52.21 | -25.21 | 32.14 | 45.28 | 74.00 | 21.79 | V |
| 2446.000 | 52.64 | -24.70 | 32.18 | 45.15 | 74.00 | 21.36 | H |
| 4882.000 | 39.87 | -32.18 | 34.24 | 37.82 | 74.00 | 34.13 | H |
| 7323.000 | 42.13 | -29.41 | 35.75 | 35.79 | 74.00 | 31.87 | H |
| 9764.000 | 43.65 | -28.13 | 37.07 | 34.70 | 74.00 | 30.36 | H |
| 12205.000 | 46.63 | -25.95 | 38.71 | 33.87 | 74.00 | 27.37 | V |

GFSK 2480MHz

| Frequency (MHz) | Measurement Result (dBuV/m) | Cable Loss (dB) | Antenna Factor (dB/m) | Receiver Reading (dBuV) | Limit (dBuV/m) | Margin (dB) | Antenna Pol. (H/V) |
|-----------------|-----------------------------|-----------------|-----------------------|-------------------------|----------------|-------------|--------------------|
| 2485.150 | 53.64 | -24.53 | 32.20 | 45.97 | 74.00 | 20.36 | V |
| 2486.050 | 54.98 | -24.51 | 32.20 | 47.29 | 74.00 | 19.02 | V |
| 4960.000 | 39.75 | -31.90 | 34.10 | 37.55 | 74.00 | 34.25 | V |
| 7440.000 | 43.05 | -28.77 | 35.68 | 36.14 | 74.00 | 30.95 | V |
| 9920.000 | 44.27 | -28.05 | 37.34 | 34.98 | 74.00 | 29.73 | V |
| 12400.000 | 44.36 | -27.32 | 38.70 | 32.99 | 74.00 | 29.64 | H |

Conclusion: PASS

Note: the spurious emission above 18G is noise only and did not show on the report.

Band edge compliance

| Mode | Channel | Frequency Range | Test Results | Conclusion |
|------|---------|------------------|--------------|------------|
| GFSK | 0 | 2.31GHz ~2.43GHz | Fig.18 | P |
| | 39 | 2.45GHz ~2.5GHz | Fig.19 | P |

Conclusion: PASS

Test graphs as below




Fig.18. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off, 2.31 GHz – 2.43GHz




Fig.19. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off, 2.45 GHz - 2.50GHz

B.6. 6dB Bandwidth

Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) = 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

| Standard | Limit |
|------------------------------|----------------------|
| FCC 47 CFR Part 15.247(a)(2) | $\geq 500\text{KHz}$ |

Measurement Results:

For GFSK

| Channel No. | Frequency (MHz) | 6dB Bandwidth (kHz) | | Conclusion |
|-------------|-----------------|---------------------|--------|------------|
| 0 | 2402 | Fig.20 | 666.00 | P |
| 19 | 2440 | Fig.21 | 667.50 | P |
| 39 | 2480 | Fig.22 | 664.50 | P |

Conclusion: PASS

Test graphs as below:




Fig.20. 6dB Bandwidth: GFSK, 2402 MHz




Fig.21. 6dB Bandwidth: GFSK, 2440 MHz




Fig.22. 6dB Bandwidth: GFSK, 2480 MHz

B.7. Maximum Power Spectral Density Level

Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.10.2

1. Set the RBW = 3 kHz.
2. Set the VBW = 10 kHz.
3. Set the span to 2 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

| Standard | Limit |
|---------------------------|-----------------------------|
| FCC 47 CFR Part 15.247(e) | $\leq 8.0 \text{ dBm/3kHz}$ |

Measurement Results:

For GFSK

| Channel No. | Frequency (MHz) | Maximum Power Spectral Density Level(dBm/3kHz) | | Conclusion |
|-------------|-----------------|--|--------|------------|
| 0 | 2402 | Fig.23 | -19.45 | P |
| 19 | 2440 | Fig.24 | -18.71 | P |
| 39 | 2480 | Fig.25 | -19.41 | P |

Test graphs as below:



Fig.23. Maximum Power Spectral Density Level Function: GFSK, 2402 MHz



Fig.24. Maximum Power Spectral Density Level Function: GFSK, 2440 MHz



Fig.25. Maximum Power Spectral Density Level Function: GFSK, 2480 MHz

B.8. AC Powerline Conducted Emission

Summary

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section

Method of Measurement:

See Clause 6.2 of ANSI C63.10 specifically.

See Clause 4 and Clause 5 of ANSI C63.10 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver:
Quasi-Peak / Average Detector.


The measurement bandwidth is:

| | |
|-----------------------------|------------------|
| Frequency of Emission (MHz) | RBW/IF bandwidth |
| 0.15-30 | 9kHz |

Test Condition:

| | |
|-------------|----------------|
| Voltage (V) | Frequency (Hz) |
| 120 | 60 |

Test setup



Measurement Result and limit:
Bluetooth (Quasi-peak Limit)

| Frequency range (MHz) | Quasi-peak Limit (dBμV) | Result (dBμV) | | Conclusion |
|--|----------------------------|---------------|------------|------------|
| | | With charger | | |
| | | bluetooth | Idle | |
| 0.15 to 0.5 | 66 to 56 | Fig.B.8.1 | Fig. B.8.2 | P |
| 0.5 to 5 | 56 | | | |
| 5 to 30 | 60 | | | |
| NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz. | | | | |

Bluetooth (Average Limit)

| Frequency range (MHz) | Average Limit (dBμV) | Result (dBμV) | | Conclusion |
|--|-------------------------|---------------|------------|------------|
| | | With charger | | |
| | | bluetooth | Idle | |
| 0.15 to 0.5 | 56 to 46 | Fig.B.8.1 | Fig. B.8.2 | P |
| 0.5 to 5 | 46 | | | |
| 5 to 30 | 50 | | | |
| NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz. | | | | |

Conclusion: Pass
Test graphs as below:




Fig.B.8.1 AC Powerline Conducted Emission- BLE

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

| Frequency (MHz) | QuasiPeak (dB μ V) | Meas. Time | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) | Comment |
|-----------------|------------------------|------------|-----------------|--------|------|------------|-------------|--------------------|---------|
| 0.190500 | 33.9 | 2000.0 | 9.000 | On | L1 | 20.0 | 30.2 | 64.0 | |
| 0.429000 | 33.5 | 2000.0 | 9.000 | On | L1 | 20.1 | 23.7 | 57.3 | |
| 1.005000 | 32.6 | 2000.0 | 9.000 | On | L1 | 19.9 | 23.4 | 56.0 | |
| 1.810500 | 28.3 | 2000.0 | 9.000 | On | N | 20.0 | 27.7 | 56.0 | |
| 4.578000 | 36.0 | 2000.0 | 9.000 | On | L1 | 19.8 | 20.0 | 56.0 | |
| 9.730500 | 39.2 | 2000.0 | 9.000 | On | L1 | 19.9 | 20.8 | 60.0 | |

Final Result 2

| Frequency (MHz) | CAverage (dB μ V) | Meas. Time | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) | Comment |
|-----------------|-----------------------|------------|-----------------|--------|------|------------|-------------|--------------------|---------|
| 0.190500 | 20.7 | 2000.0 | 9.000 | On | L1 | 20.0 | 33.3 | 54.0 | |
| 0.429000 | 19.7 | 2000.0 | 9.000 | On | N | 20.1 | 27.6 | 47.3 | |
| 1.005000 | 23.0 | 2000.0 | 9.000 | On | L1 | 19.9 | 23.0 | 46.0 | |
| 1.810500 | 24.5 | 2000.0 | 9.000 | On | L1 | 19.8 | 21.5 | 46.0 | |
| 4.902000 | 27.8 | 2000.0 | 9.000 | On | L1 | 19.9 | 18.2 | 46.0 | |
| 8.857500 | 29.7 | 2000.0 | 9.000 | On | L1 | 19.9 | 20.3 | 50.0 | |




Fig.B.8.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

| Frequency (MHz) | QuasiPeak (dBμV) | Meas. Time | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|------------------|------------|-----------------|--------|------|------------|-------------|--------------|---------|
| 0.213000 | 35.9 | 2000.0 | 9.000 | On | L1 | 20.0 | 27.2 | 63.1 | |
| 0.447000 | 36.2 | 2000.0 | 9.000 | On | L1 | 20.1 | 20.8 | 56.9 | |
| 0.987000 | 33.5 | 2000.0 | 9.000 | On | L1 | 19.9 | 22.5 | 56.0 | |
| 1.774500 | 28.4 | 2000.0 | 9.000 | On | N | 20.0 | 27.6 | 56.0 | |
| 4.951500 | 37.2 | 2000.0 | 9.000 | On | L1 | 19.9 | 18.8 | 56.0 | |
| 8.839500 | 32.6 | 2000.0 | 9.000 | On | N | 20.1 | 27.4 | 60.0 | |

Final Result 2

| Frequency (MHz) | CAverage (dBμV) | Meas. Time | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|-----------------|------------|-----------------|--------|------|------------|-------------|--------------|---------|
| 0.213000 | 23.8 | 2000.0 | 9.000 | On | L1 | 20.0 | 29.3 | 53.1 | |
| 0.447000 | 27.2 | 2000.0 | 9.000 | On | L1 | 20.1 | 19.7 | 46.9 | |
| 0.987000 | 24.0 | 2000.0 | 9.000 | On | L1 | 19.9 | 22.0 | 46.0 | |
| 1.788000 | 25.1 | 2000.0 | 9.000 | On | L1 | 19.8 | 20.9 | 46.0 | |
| 4.951500 | 28.4 | 2000.0 | 9.000 | On | L1 | 19.9 | 17.6 | 46.0 | |
| 8.839500 | 29.4 | 2000.0 | 9.000 | On | L1 | 19.9 | 20.6 | 50.0 | |



B.9. Antenna Requirement

The antenna of the device is permanently attached. There are no provisions for connection to an external antenna.

The unit complies with the requirement of FCC Part 15.203.

B.10. Duty cycle

Method of Measurement:


Use the following spectrum analyzer settings:

- Span = zero span
- RBW = 100kHz
- VBW \geq RBW
- Sweep = single sweep
- Detector function = peak

Measurement Results:

| Channel No. | Frequency (MHz) | Duty cycle | |
|-------------|-----------------|------------|------|
| 19 | 2440 | Fig.26 | 0.86 |

See test graphs as following.



Date: 25.JAN.2000 06:17:49

Fig.26. Duty cycle: BLE 2440 MHz

ANNEX C: Accreditation Certificate



*****END OF REPORT*****