

RFCBA040302IMAB301

History List

[illegible]

1.Explanation of part number :

RF	CBA	0403	02	I	M	A	B	3	01
Type Code	Product Code	Connector Dimension (Unit: mm)	Cable Length (unit: cm)	Connector Brand	Type of Connector	Application	Project status	Wire Diameter	Project
Walsin RF Device	CBA: Cable Assembly	Per 2 digits of length, width e.g.:0403 Length 4.7mm, Width 3.0mm	2 digits for cable length e.g.: 02 Length 2.7cm	A: N C:MCX D:IPEX III E: IPEX IV F: IPEX A13 H: Hirose I: IPEX M: MMCX S: SMA T: TNC U:MURATA N: None	A: Reverse Female B: Reverse Male F: Female M: Male N: None	0: 0GHz 3: 3GHz 5: 5 GHz 6: 6GHz A: 2.4GHz ISM band B: GSM 900/1800 dual band G: GPS band L: 2.4/5.2/5.8 GHz tri-band N: NFC T:LTE band W: WCDMA band	B: MP T:During Test X: Pile Run	0:None 1: 0.81 2: 1.32 3: 1.13 4:Low Loss 1.13 5: 0.50 6:RG316 7: 1.37 8:RG178 9:Low Loss 1.37 A:RG174 B:RG178 單芯線	01~99 series number

2.Electrical Specification :

Item	Specification
Frequency Range	2.4 ~ 2.5 GHz
Return Loss	-3dB(Max)
VSWR	6 max.
Peak Gain	-0.80 dBi
Polarization	Linear
Radiation Pattern	Omni-directional
Impedance	50Ω
Operation Temperature	-20℃ ~ +65℃

UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301


DOCUMENT
NO.

ENS070028440-000899910250

SPEC REV.

A0

3. Antenna Drawing :



UNLESS OTHER SPECIFIED TOLERANCES ON :

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301

DOCUMENT
NO.


ENS070028440-000899910250

SPEC	REV.
A0	

4. Performance Report :

Test Report

■ Experimental Setup



Antenna Solution Detail



UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301

DOCUMENT
NO.


ENS070028440-000899910250

SPEC REV.

A0

ELECTRICAL CHARACTERISTICS

Return Loss



UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301


DOCUMENT
NO.

ENS070028440-000899910250

SPEC REV.
A0

■ Antenna Efficiency & Peak Gain

2400 ~ 2500 MHz



Antenna Efficiency and Peak Gain

Frequency (MHz)	Antenna	
	Efficiency (%)	Peak gain (dBi)
2400	23.06	-1.59
2450	24.09	-1.55
2500	25.28	-0.80

UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301

DOCUMENT
NO.





ENS070028440-000899910250

SPEC REV.

A0

RADIATION PATTERN

2400 ~ 2500 MHz



Frequency [MHz]	ZX plane		ZY plane		XY plane	
	Max Value [dBi]	Average [dBi]	Max Value [dBi]	Average [dBi]	Max Value [dBi]	Average [dBi]
2400	-3.33	-6.02	-1.68	-6.70	-4.02	-6.84
2450	-3.23	-5.90	-1.60	-6.50	-3.81	-6.67
2500	-3.23	-6.28	-0.88	-5.80	-4.71	-6.61

UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A

ANGLES = N/A

HOLEDIA = N/A

SCALE : N/A

UNIT : mm



INPAQ TECHNOLOGY (SUZHOU) CO., LTD
No.5, Chunqiu Road, Panyang Industrial Park
Huangdai Town, Xiangcheng Zone, Suzhou

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFCBA040302IMAB301

DOCUMENT
NO.

ENS070028440-000899910250

SPEC REV.

A0