MilDef Crete Inc. 7F, No.250, Sec.3, Pei Shen Rd., Shen Keng District, New Taipei City Taiwan R.O.C.

Federal Communications Commission Authorization and Evaluation Division Equipment Authorization Branch 7435 Oakland Mills Road Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product Product description: Notebook Computer

Model No: RV11

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product : Notebook Computer

will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21403-13993-C-1

and the accompanying calculations.

Company: Mildef Crete Inc.

Address: 7F, No.250, Sec.3, Pei Shen Rd., Shen Keng District, New Taipei City

Taiwan R.O.C.

N)illie

Date: 14.10.2014

Signature :



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21403-13993-C-1

FCC ID: IR5RV11

3.2 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a "worst case" or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

5.8GHz

Item	Unit	Value	Remarks
P	mW	54.56	Peak value
D	dB		
AG	dBi	6.56	
G		4.53	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.049	Calculated value

2.4GHz

Item	Unit	Value	Remarks
P	mW	60.87	Peak value
D	dB		
AG	dBi	4.83	
G		3.04	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.037	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure			
Frequency (MHz)	Power Density (mW/cm ²)		
1500 – 100.000	1.0		





