

客戶名稱 : 系統電子
CUSTOMER

Documnet No.: ENS000160410

Approval Sheet Rev.: A1

Spec. Rev. : P1

承認書

APPROVAL SHEET

產品品名/Product Model No. : WA-M-LB-02-262 (WIFI Main)

客戶料號/Customer No. : 354-0302020-011

案名/Model Name: Butterfly

發行日期/ Issue Date : 2022/1/24

承認日期/ Approved Date :

Approved by customer: (signing or stamping here)

簡弘期 2022.01.25



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.


☒ 350 苗栗縣竹南鎮公義里11鄰科義街11號 ☐ 428 台中市大雅區科雅路27號4樓
電話 : 037-585-555 電話 : 04-2560-6555
傳真 : 037-585-511 傳真 : 04-2560-5151

No. 11, Ke-Yi St., Chunan, Miaoli 350,
Taiwan, R.O.C.
Tel. : +886-37-585-555
Fax : +886-37-585-511

4F, No. 27, Keya Road, Daya Dist., Taichung City
428, Taiwan, R.O.C.
Tel. : +886-4-25606555
Fax : +886-4-25605151

Embedded Dual-Band Antenna for WA-M-LB-02-262

1. Explanation of part number :



(1) Product type : Wireless Antenna

(2) Material : Metal

(3) Frequency : 2400~2500;5150~5850 MHz

(4) Coaxial Cable Type : Black Coaxial Cable

(5) Suffix : 262

2. Electrical Specification :

Those specifications were specially defined for **Butterfly** model, and all characteristics were measured under the model's handset testing.

2-1. Frequency Band :

Band Type	Frequency (MHz)
Dual-Band	2400-2500;5150~5850 MHz

2-2. Impedance :

50 ohm nominal

2-3. Matching circuit :

None

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
WA-M-LB-02-262


DOCUMENT
NO.

ENS000160410

SPEC REV.
P1

2-4. Return loss/VSWR :

Frequency(MHz)	2400	2450	2500	5150	5850
Main VSWR(dB)	1.48	1.16	1.13	1.62	1.86



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易喧

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262

DOCUMENT
 NO.

ENS000160410

SPEC REV.
 P1

3. Antenna Drawing :



NOTE:

1. 工程圖上 * 為重點尺寸標註指示
Mark * are the key dimensions.
2. 工程圖上 # 為Cpk量測尺寸標註指示
Mark # are CPK dimensions.

REV.P2

ITEM	DESCRIPTION	MATERIAL SPECIFICATION	QUANTITY	UNIT	Supplier	UL File NO.
1	Metal	35.4x12x4.5mm	1	PCS	HA0278	N/A
2	Adhesive (3M9888T)	29.5x10.4x0.15mm	1	PCS	HA0026	N/A
3	Cable	OD 1.13 Low Loss Black	1	PCS	HA0008	E318898
4	Connector	I-PEX MHF4-L I-PEX Equivalent(compatible)	1	PCS	HA0063	E213445
5	Tube	OD1.5*20mm	1	PCS	HA0059	N/A

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易喧

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
WA-M-LB-02-262

DOCUMENT
NO.

ENS000160410


SPEC REV.
P1

4. Gain and Radiation Pattern

4-1.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-1.2 Chamber definition



1. An anechoic chamber (10mx3mx3m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 50cmx50cmx50cm at the center of rotator
3. The distance between DUT and standard antenna is 9.14m
4. Two measurement antennas is 3164-06 (300MHz - 6GHz) and 3164-05 (2 - 18GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262

DOCUMENT
 NO.

ENS000160410

SPEC REV.
 P1

4-1.3 Gain data and radiation pattern

Antenna gain is marked (dBi) and is based on **STANDARD HORN** antenna. The data shows Peak-Gain and Efficiency.

Frequency (MHz)	Main Gain Data	
	Peak Gain (dBi)	Efficiency (%)
2400	2.18	39.23
2450	2.44	42.99
2500	2.06	44.76
5150	3.37	37.41
5250	3.74	40.74
5350	3.44	41.04
5470	3.29	39.87
5600	3.52	44.83
5725	3.75	45.91
5780	3.57	46.64
5850	4.08	45.4

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
WA-M-LB-02-262


DOCUMENT
NO.

ENS000160410

SPEC REV.
P1


2400-2500MHz radiation characteristic

Main antenna: 2400 MHz




Center Frequency	2400 MHz
Three-dimensional (dBi) peak	2.18

Main antenna: 2450 MHz



Center Frequency	2450 MHz
Three-dimensional (dBi) peak	2.44

Main antenna: 2500 MHz



Center Frequency	2500 MHz
Three-dimensional (dBi) peak	2.06

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262


DOCUMENT
 NO.

ENS000160410


SPEC REV.
 P1

5150-5850MHz radiation characteristic**Main antenna: 5150 MHz**

Center Frequency	5150 MHz
Three-dimensional (dBi) peak	3.37

Main antenna: 5250 MHz

Center Frequency	5250 MHz
Three-dimensional (dBi) peak	3.74

Main antenna: 5350 MHz

Center Frequency	5350 MHz
Three-dimensional (dBi) peak	3.44

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±

**INPAQ TECHNOLOGY CO., LTD.**

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262

DOCUMENT
 NO.

ENS000160410


SPEC REV.
P1

Main antenna: 5470 MHz




Center Frequency	5470 MHz
Three-dimensional (dBi) peak	3.29

Main antenna: 5600 MHz



Center Frequency	5600 MHz
Three-dimensional (dBi) peak	3.52

Main antenna: 5725 MHz



Center Frequency	5725 MHz
Three-dimensional (dBi) peak	3.75

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262

DOCUMENT
 NO.

ENS000160410


SPEC REV.
 P1

Main antenna: 5785 MHz



Center Frequency	5785 MHz
Three-dimensional (dBi) peak	3.57

Main antenna: 5850 MHz



Center Frequency	5850 MHz
Three-dimensional (dBi) peak	4.08

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY:周敬晨

CHECKED BY:鄭榮謀

DESIGNED BY:林易暄

APPROVED BY:張建焜

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
 WA-M-LB-02-262

DOCUMENT
 NO.

ENS000160410

SPEC REV.
 P1